

## 8000T Semi-Gloss Removable

<b>Media Type</b>	Label	✓	<b>Adhesive Type</b>	Permanent	
	Receipt			Removable	✓
	Tag			No Adhesive	
	Wristband		<b>Environment</b>	Indoor	✓
<b>Material Type</b>	Paper	✓		Outdoor	
	Synthetic		<b>Properties</b>	Cold Temperature	✓
<b>Printing Technology</b>	Direct Thermal (no Ribbon Required)			Deep Freeze	
	Thermal Transfer (Ribbon Required)	✓		High Temperature	
<b>Finish</b>	Matte			Ultra High Temperature	
	Gloss	✓		High Tack	
			Chemical Resistance	-	

### Additional Features

- Good adhesion and clean removability on a wide variety of surfaces
- Produces good quality small detailed barcodes with Zebra 2300 and 2100 ribbons
- Adhesive complies with European food regulations and BfR Recommendation XIV for direct contact with dry, moist and fatty foodstuffs which have a reduction factor of at least 3
- Adhesive complies with FDA 175.105 for direct contact with dry foodstuffs, or alternatively separated by a functional barrier
- BPA free
- Latex free adhesive

### Suggested Applications

- Removable labelling of packaging materials e.g. boxes, pallets, tote bins in logistic applications
- Product identification
- Removable work-in-progress labels
- Removable shelf-edge labelling
- Removable price of promotional labels
- Process labelling

## Technical Specifications

	Description	Caliper
<b>Facestock</b>	Semi-gloss white paper	69 microns
<b>Adhesive</b>	Removable acrylic adhesive	13 microns
<b>Liner</b>	57gsm glassine liner	51 microns
	<b>Total</b>	<b>133 microns ±10%</b>

**Recommended Zebra Printers:** Desktop, mid-range and high-performance printers

**Recommended Ribbons:** 2300, 2100, 3400, 3200

**Minimum Application Temperature:** -15°C  
When the label is applied, the environment and surface should be above this temperature

**Service Temperature Range:** -30°C to 80°C  
Following correct application and appropriate dwell time (usually 24hrs) the media will withstand this temperature range

**Recommended Storage Conditions:** 1 year duration when stored at 20°C to 25°C at 40% to 50% RH  
Storage of product before use

**Expected Life Span in Application:** Indoor use, for up to 1 year  
Following correct application and appropriate dwell time (usually 24hrs) we expect, but do not warrant, a life span as indicated

## Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

For testing of this material, please order sample roll SAMPLE5413.